HP USB-C 65W Laptop Charger (671R2AA)



Overview

Charge your World

Charge most USB-C® devices with just one compact charger. The HP 65W USB-C Laptop Charger provides up to 65W of power, enough for almost any USB-C® device.

Charges Big or Small

Now with smart power that adapts to your charging needs, this laptop charger delivers 15W, 27W, 60W, or 65W of power[1]. This will be the only charger you'll want in your bag.

Travel-Size

This compact, lightweight charger comfortably fits in your bag without weighing it down. The durable cable and built-in cable management keeps you organized when traveling or commuting.

A Universal Solution

Enjoy the flexibility to charge most USB-C® devices[1], whether it's your laptop, tablet, or phone.

---

[1] Compatible with most devices that charge using USB-C®. Non-HP listed compatible products tested internally by HP.

Specifications

Dimensions (W x D x H)	3.82 x 2.11 x 0.83 in
Weight	0.46 lb
Minimum System Requirements	USB Type-C® port
UPC number	(AB0) 196548308217; (AB1) 196548308224; (AB2) 196548308231; (ABA) 196548308248; (ABB) 196548308255; (ABG) 196548308262; (ABJ) 196548429356; (ABM) 196548308293; (ABT) 196548308309; (ABU) 196548308316; (ABY) 196548308323; (ABZ) 196548308330; (AC4) 196548308347; (AC8) 196548308354; (ACB) 196548424443; (ACJ) 196548308361; (ACQ) 196548308378; (AKH) 196548308385; (AKL) 196548308392; (AR6) 196548308408; (UUF) 196548308415; (UUZ) 196548308422
Manufacturer Warranty	HP standard one-year limited warranty.
What's in the box	AC power adapter; USB Type-C® cable; 1 Power Cord; Warranty Card

Additional specifications

Cable length (imperial)	39.37 in (power cord); 70.9 in (USB Type-C® cable)
Certifications and compliances	CE Mark; IEC 60950-1; EN 60950-1; UL 60950-1; UL 62368-1; SELV; C-UL-US; DENAN; EN 55022 Class B; FCC Class B; CCC; NOM-1 NYCE; NORDICS; CISPR 22 Class B; MTBF
Compatibility	Compatible with most USB-C® devices
Compatibility disclaimer 1	Host USB-C power delivery required for power delivery
Connection type	USB Type-C®
Connector description	USB Type-C®
Datasheet photo 1	https://hp.widen.net/content/pi7ikptvx7/png/HP%2065W%20USB-C%20Laptop%20Charger_Top%20Down_M1850698.png?w=800&h=800&position=c&color=ffffff00&quality=80&u=dlkxlp
Datasheet photo 2	https://hp.widen.net/content/l6lyqbkzfi/png/HP%2065W%20USB-C%20Laptop%20Charger_Top_M1850701.png?w=800&h=800&position=c&color=ffffff00&quality=80&u=dlkxlp
Datasheet photo 3	https://hp.widen.net/content/gqv0dhenqe/png/HP%2065W%20USB-C%20Laptop%20Charger_Rear_M1850699.png?w=800&h=800&position=c&color=ffffff00&quality=80&u=dlkxlp
End of Life CO2e (kg)	0.1
Energy Usage CO2e (kg)	3
Hold-up time	5 ms at 115 VAC input
Input efficiency	89% min at 115 VAC/230 VAC at 20V/3.25A
Input frequency	47-63 Hz
Input operating current	1.6 A at 90 VAC max
Master carton dimension (imperial)	23.46 x 7.76 x 9.84 in
Master carton weight (imperial)	13.93 lb
Non-Operating Humidity Range	10 to 95% RH
Operating altitude	Up to 16,400 ft
Operating humidity range	20 to 95% RH (non-condensing)
Operating temperature range	0 to 35°C
Operating temperature range	32 to 95°F
Output current limit	8 A max
Output power	65 W
Output voltages	5V/9V/12V/15V/20V
Over-voltage protection	20V: 29V
Package dimensions (W x D x H)	3.82 x 2.95 x 9.33 in
Package weight	1.1 lb

Pallet weight	668.79 lb
Production CO2e (kg)	3
Storage temperature range	-20 to 85°C
Storage temperature range	-4 to 185°F
Total CO2e (kg)	10
Transportation CO2e (kg)	0.1
UNSPSC code	39121006

Disclaimer — Copyright

USB Type-C® and USB-C® are trademarks of USB Implementers Forum.