



Poly Trio C60 IP Conference Phone for Microsoft Teams Full Radio and PoE-enabled (849B6AA)

Overview

One device. Many possibilities.



Bring people together. Launch big ideas. And make sure everyone at the table can be heard, near or far with Poly signature audio. The Trio C60 plays nicely with everyone, delivering native experiences on your favorite collaboration platforms.

Poly signature audio

Get more out of your conference calls. Poly reduces distracting background noise to ensure every inflection is heard. Hear every reaction with up to 22 kHz of rich, full sound.

One-touch join

All it takes is a fingertip to get started. Join your calls in a second with a single touch of a button thanks to the truly intuitive user experience.

Features

Flexible connectivity

Maximize flexibility and investments with connectivity to multiple SIP and UC-cloud services simultaneously.

Audio clarity

Experience the power of full-duplex audio for natural conversations. Count on audio clarity in any size space with echo and reverb cancellation.

Poly portfolio compatible

Complement your Poly Studio X50, Poly Studio X30, or G7500 video solution with fast, simple control from Trio C60.

Scalable

Cater to any size meeting with optional expansion microphones or by daisy-chaining multiple systems together.

Wi-Fi calling

Get started faster and more easily with Wi-Fi audio calling (2.4–5 GHz), with no need to re-cable.

Certified for Microsoft Teams

Experience seamless collaboration with Microsoft Teams —the Trio C60 is certified right out of the box.

Specifications

Display size (diagonal)	12.7 cm (5")
Display size (diagonal)	5"
Panel technology	Color LCD
Audio	Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression; Comfort noise generation; DTMF tone generation (RFC 2833 and in-band); Low delay audio packet transmission; Adaptive jitter buffers
Dimensions (W x D x H)	38.3 x 7.5 x 33.2 cm
Dimensions (W x D x H)	15.1 x 2.9 x 13.1 in
Weight	950 g
Weight	2.1 lb
Ports	1 USB 2.0 Type-A (for USB battery charging); 1 USB 2.0 Micro-B (for USB audio device); 2 RJ-45 (10/100/1000BASE-TX Mbps)
Package dimensions (W x D x H)	48.3 x 11.5 x 39.4 cm
Package weight	300 g
Energy star certified	ENERGY STAR® certified
Special features	Unicode UTF-8 character support
Security management	802.1X Authentication and EAPOL Media encryption via SRTP; Digest authentication; Encrypted configuration files; HTTPS secure provisioning; Password login; Support for signed software executables; Support for URL syntax with password; Transport Layer Security (TLS); Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2); FIPS 140-2 compliant cryptographic module
UPC number	197497506525
Manufacturer Warranty	Poly standard one-year limited warranty
What's in the box	Setup sheet; Console; Network (LAN) cable-CAT-5E; Cable wrap; Tactile overlay for improved accessibility

Additional specifications

Aspect ratio	16:9
Audio codecs	G.711 (A-law and μ -law); G.722; G.722.1; G.722.1C; G.729AB; G.719; Polycom® Siren™ 7; Siren™ 14; iLBC; OPUS
Cartons per layer	4
Cartons per pallet	12
Certifications and compliances	AS/NZS 60950-1; AS/NZS 62368-1-17; Australia -AS/NZ4268; Australia A&C Tick; CAN/CSA C22.2 No. 60950-1-03; CAN/CSA C22.2 No. 62368-1-14; CE Mark; CISPR22 Class B; EN 301 489-1, EN 301 489-3, EN 301 489-17; EN 61000-3-2; EN 61000-3-3; EN 62368-1; ETSI EN 300 328 v1.9.1; ETSI EN 300 330; ETSI EN 301 893 v1.7.1; FCC Part 15 (CFR 47) Class B; FCC Part 15.225; FCC Part 15.247; FCC Part 15.407; ICES-003 Class B; IEC 60950-1; IEC 62368-1; Japan Item (19); Japan Item (19)-3; Japan Item (19)-3-2; Japan MIC/VCCI Class B; NZ Telepermit; ROHS compliant; RSS 247 Issue 1; UL 60950-1; UL 62368-1
Certified collaboration software	Microsoft Teams; Skype for Business
Color	Black
Datasheet photo 1	AHID/7c001d32f050de3e5ce25c495c999d264d3d68d5
Datasheet photo 2	AHID/b6ef83701b13edb970a45cd2c6dd9c8c282b0f50
Datasheet photo 3	AHID/d7d3b4c12ad5e97844485e9674494472a5d1c6a1
Display features	On-screen virtual keyboard
ECCN	5A992
End of Life CO2e (kg)	0.4
Energy Usage CO2e (kg)	12
HTS code	8517180050
Headset and handset compatibility	Bluetooth® headset compatibility
Layers per pallet	3
Management Software	Poly Zero Touch Provisioning; RealPresence Resource Manager (v. 10.1 or above) based provisioning; Polycom Device Management Service for Enterprise (PDMS-E); Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management; SDP
Master carton dimension (imperial)	9.64 x 17.32 x 11.61 in
Master carton dimension (metric)	24.5 x 44 x 29.5 cm
Master carton weight (imperial)	29.23 lb
Master carton weight (metric)	13.26 kg
Microphone type	Three cardioid microphones
Multiple order quantity	5
Native resolution	720 x 1280

Network protocols, supported	DHCP VLAN discovery; LLDP-MED for VLAN discovery; FTP/TFTP/HTTP/HTTPS server-based central provisioning; Manual or dynamic host configuration protocol (DHCP) network setup; QoS Support — IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP; Time and date synchronization using SNTP; Provisioning and call server redundancy support
Operating humidity range	5 to 95%
Operating temperature range	0 to 40°C
Operating temperature range	32 to 104°F
Package dimensions (W x D x H)	7.48 x 8.26 x 2.16 in
Package weight	0.66 lb
Pallet dimensions	40 x 48 x 58.66 in
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Pallet weight	357 kg
Pallet weight	787.05 lb
Power	LAN IN: Built-in auto-sensing IEEE 802.3at, PoE Device (Class 4); LAN OUT: Built-in auto-sensing IEEE 802.3af power sourcing equipment ^[1]
Production CO2e (kg)	52
Products per pallet	60
Products per pallet layer	20
Sensitivity (speaker)	92 dB
Storage temperature range	-20 to 70 °C
Storage temperature range	-40 to 158°F
Telephony and call handling features	Bundled with Polycom UC Software: Corporate Directory Access using LDAP; Call timer and call waiting; Call transfer, hold, divert (forward), park, pickup; Called, calling, connected party information; Distinctive incoming call treatment/call waiting; Do not disturb function; Local configurable digit map/dial plan; Local five-way audio conferencing; Shared call/bridged line appearance; Visual Conference Management; Up to 3 lines (maximum one Skype for Business and Microsoft Teams); Daisy-chain up to four; One-touch speed dial, redial and meeting join
Total CO2e (kg)	70
Touch-enabled	Gesture-based, multi-touch capable touchscreen
Transportation CO2e (kg)	0.5
UNSPSC code	43191511
VoIP features	IETF SIP (RFC 3261 and companion RFCs)
Wireless range	Up to 6.1 m
Wireless range (imperial)	Up to 20 ft
Wireless technologies	Bluetooth® 4.2; Wi-Fi network connectivity: 2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20); 5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)

[1] Requires full Class 4 power input on LAN IN for operation

Communication & Collaboration

★ : Recommended

Poly Support Services

1 Year Partner Poly+ Analyze Trio C60	UQ7U9PB
1 Year Partner Poly+ Onsite Poly Trio C60	P86240158
1 Year Partner Poly+ Trio C60	P86240160
1 Year Poly Elite Onsite Trio C60	E86240114
1 Year Poly Elite Trio C60	E86240112
1 Year Poly+ Onsite Trio C60	P86240114
1 Year Poly+ Trio C60	P86240112
3 Year Partner Poly+ Analyze Trio C60	UQ7V0PB
3 Year Partner Poly+ Onsite Poly Trio C60	P86240358
3 Year Partner Poly+ Trio C60	P86240362
3 Year Poly+ Onsite Trio C60	P86240314
3 Year Poly+ Trio C60	P86240312
Upg emb 3yr Ptr Poly+ to 3yr Partner Poly+ Analyze Trio C60	UQ7V4PB
Upg emb 3yr Ptr Poly+ to 3yr Poly+ Analyze OS Trio C60	UQ7V5PB
Upg emb 3yr Ptr Poly+ to 3yr Poly+ Analyze Trio C60	UQ7V3PB

Disclaimer — Copyright

© Copyright 2026 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.