



HP 45W USB-C LC Power Adapter (1MZ01AA)

Overview

Simple, affordable Chromebook™ charging through USB-C®.

Power and charge your HP Chromebook[1] from its USB-C® port with the HP 45W USB-C LC Power Adapter.

Easy to use

Connect one end of the adapter to the USB-C® port on your device[1], and plug the AC head into any available wall outlet.

World-class support

Rest easy with a one-year limited warranty.

Carry and store with your device

Pack the compact adapter inside your device's carrying case for easy, convenient charging and power whenever you need it.

[1] See Product QuickSpecs for device compatibility.

Specifications

Product Dimensions W x D x H (metric)	94 x 40 x 26.5 mm
Product Dimensions W x D x H (imperial)	3.7 x 1.57 x 1.04 in
Weight (metric)	193 g
Weight (imperial)	0.43 lb
System Requirements, Minimum	USB Type-C® port
UPC Number	(AB1) 196548449521; (AB2) 196548449545; (ABA) 190781650966; (ABB) 196548449552; (ABG) 196548449576; (ABJ) 196548458080; (ABT) 196548449606; (ABU) 196548449637; (ABY) 196548449668; (ABZ) 196548449682; (AC4) 196548449729; (ACB) 196548449767; (ACJ) 196548449798; (ACQ) 196548449811; (AKH) 195161323522; (UUF) 196548449859; (UUZ) 196548449897
Manufacturer Warranty	One-year limited warranty.
What Is In The Box	AC power adapter; 1 power cord; warranty card

Additional specifications

Cable Length (imperial)	70.87 in (power cord)
Cable Length (metric)	180 cm (power cord)
Certifications and Compliances	CE Mark; IEC 60950-1; EN 60950-1; UL 60950-1; SELV; C-UL-US; DENAN; EN 55022 Class B; FCC Class B; CCC; NOM-1 NYCE; NORDICS; CISPR 22 Class B; MTBF
Compatibility Statement	Compatible with HP Chromebook PCs with USB-C® port
Connection Type	4.5 mm barrel port
Connector Description	USB Type-C™
Datasheet Photo 01	AHID/eac1d1c143cba5e4f32866838c8de5eb76f1328e
Hold-up Time	5 ms at 115 VAC input
Input Efficiency	89% min at 115 VAC/230 VAC at 15V/4.33A; 87.73% min at 115 VAC/230 VAC at 15V/4.33A
Input Frequency	47-63 Hz
Input Operating Current	1.4 A at 90 VAC max
Input Voltage	45 W
Non-operating Humidity Range	10 to 95% RH
Operating Altitude (imperial)	Up to 16,400 ft
Operating Altitude (metric)	Up to 5,000 m
Operating Humidity Range	20 to 95% RH (non-condensing)
Operating Temperature Range (celsius)	5 to 35°C
Operating Temperature Range (fahrenheit)	41 to 95°F
Output Current Limit	5 A max
Output Power	45 W
Output Voltages	5V/12V/15V
Storage Temperature Range (celsius)	-20 to 85°C
Storage Temperature Range (fahrenheit)	-4 to 185°F
UNSPSC Code	39121006

Disclaimer — Copyright

© Copyright 2026 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements

accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Aug 20, 2026 5:00 PM UTC+0000