



HP 110W USB-C Laptop Charger ()

Overview

One Charger, Two Devices

Meet the high wattage power demands of your laptop with an advanced charging solution that features 100 W of USB-C® power and an additional 10 W USB-A port for simultaneously charging a phone, tablet, or whatever else you need to power[1]. Replace your original or have a spare for the home or office.



Fast, Dynamic Charging

Power through your day with a fast, universal[1] laptop charger that delivers a huge 110 W of juice. Light and compact, it's an ideal travel companion that also offers dynamic charging (5V, 9V, 15V or 20V) based on device needs.



High Power. Lower Impact.

Compliant with the latest IEC 62368-1 safety standard, and tested with strict industry standards, this laptop charger incorporates multiple safeguards to protect you and your devices against surge, overcharging, overcurrent, and overheating. Plus, it contains 30% post-consumer recycled materials[2].



Simultaneous Multi-Device Charging

Tap into 100W of USB-C® power and an additional 10W USB-A port for simultaneously charging a phone or tablet. Works across Windows®, Mac® and Chrome platforms for maximum flexibility.

Features

Charges Almost Anything

Bring your power-hungry devices and charge quickly via a USB-C® cord and/or USB-A port. Supports almost any device and brand across Windows®, Mac®, and Chrome.^[1]

Multi-Device Charging

Say goodbye to tangled cords and carrying multiple chargers. Now you can simultaneously charge multiple devices (laptop, phone, tablet) with just one advanced charging solution.^[1]

Dynamic Charging

Dynamic power management (5V, 9V, 15V or 20V) matches device needs, minimizes charging times and reduces energy consumption.

36-Month Warranty

Experience HP quality and reliability and for added peace of mind, this laptop charger comes with a 36-month warranty.

[1] Compatible with most devices that charge using USB-C®.

[2] Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 EPEAT® standard.

Specifications

Sustainability Specifications	At least 30% post-consumer recycled plastic
System Requirements, Minimum	USB Type-C® port
What Is In The Box	AC power adapter; USB Type-C® cable; 1 Power Cord; Warranty Card ^[1]

Additional specifications

Cable Length (imperial)	39.37 in (power cable); 70.87 in (non-detachable USB-C® cable)
Cable Length (metric)	1 m (power cable); 1.8 m (non-detachable USB-C® cable)
Certifications and Compliances	CE Mark; IEC 60950-1; EN 60950-1; UL 60950-1; C-UL-US; DENAN; FCC Class B; CISPR 32 Class B; CCC; NOM-1 NYCE; NORDICS; MTBF; EN55032 Class B; EN62368-1; UL62368-1; IEN60950
Color	Black
Compatibility Statement	Supports up to 100 W power delivery
Connection Type	USB Type-C®; USB Type-A
Datasheet Photo 01	AHID/2b9adb41705ab6b4c2b7ab337043afa01fccfe9
Datasheet Photo 02	AHID/7e135c6847f8280ddd4e747772470726c240d273
Datasheet Photo 03	AHID/41e2d13cf4b459f3d87759da1042251c1b917ec9
Datasheet Photo 04	AHID/7114c3dd9d7ad9fad40409a42f45df6ffabedfbe
Hold-up Time	5 ms at 115 VAC input
Input Efficiency	89% min at 115 VAC/230 VAC at 20V/3.25A
Input Frequency	47-63 Hz
Input Operating Current	1.6 A at 90 VAC max
Operating Altitude (imperial)	Up to 16,400 ft
Operating Altitude (metric)	Up to 5,000 m
Operating Humidity Range	5 to 95%
Operating Temperature Range (celsius)	0 to 35°C
Operating Temperature Range (fahrenheit)	32 to 95°F
Output Current Limit	6.25 A max
Output Power	Up to 110 W
Output Voltages	5V/9V/12V/15V/20V
Over-Voltage Protection	20V: 29V
Storage Temperature Range (celsius)	-20 to 85°C
Storage Temperature Range (fahrenheit)	-4 to 185°F

[1] The USB Type-C® cable is attached to the AC power adapter itself and cannot be removed.

Disclaimer — Copyright

© Copyright 2026 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Sep 29, 2026 7:17 AM UTC+0000